



## VERIFICATION

This is to verify that the attached is a true translation of Japanese application filed on September 28, 2001 to the United States Patent and Trademark Office.

Serial No.:

Filing Date: September 28, 2001

Inventors: YOSHIDA, et al.

Invention: REPEATING DEVICE, TELEPHONE SET AND  
RECORDING MEDIUM

Foreign Application:

Application Number: 2000-215665

Country: Japan

Filed: July 17, 2000

October 28, 2001

Translator

Yoshiko Kawahara

Best Available Copy

[Document] Specification

[Title of the Invention] REPEATING DEVICE, TELEPHONE SET, AND  
RECORDING MEDIUM

[Claims]

[Claim 1] A repeating device for relaying communication to a plurality of receiver-side telephones connected to a local area network;

said repeating device comprising a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected receiver-side telephone to a caller-side telephone.

[Claim 2] A repeating device according to claim 1, wherein said device further comprises a function for receiving a transfer request from a user.

[Claim 3] A telephone capable of generating a call to a plurality of receiver-side telephones being connected to a local area network without designating the address of the receiver;

said telephone comprising a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and

a function for generating a call addressed to said selected telephone.

[Claim 4] A telephone connected to a local area network; said telephone comprising, upon receiving a transfer request from a user, a function for requesting a response from a plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected telephone to a caller-side telephone.

[Claim 5] A recording medium capable of being read by a computer and storing a program to be executed by said computer, said recording medium used either for a device for relaying communication to a plurality of receiver-side telephones being connected to a local area network, a telephone being connected to a local area network, or a telephone capable of generating a call to a plurality of receiver-side telephones being connected to a local area network without having to specify the address of the receiver telephone,

wherein said recording medium comprises any of the following sets of functions:

a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which

the call is to be connected, and a function for notifying the address of the selected receiver-side telephone to a caller-side telephone;

a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for generating a call addressed to said selected telephone; or

a function for requesting, upon receiving a transfer request from a user, a response from a plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected telephone to a caller-side telephone.

[Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Pertains]

The present invention relates to a repeating device, a telephone set and a recording medium, and especially relates to the communication technology of relaying via a communication line telephone devices connected to a local area network and the like.

[0002]

[Prior Art]

Heretofore, voice communication between dedicated telephone sets connectable to a local area network (hereinafter called LAN telephone sets) and voice communication between personal computers (PCs) connected to the local area network are realized by a VoIP (Voice over IP) technology that processes the voice signal into packets and transmits the packets through the network. The prior art technology is shown in FIG. 7, wherein a PC 11 and telephone sets 12a - 12c connected to the LAN 10 is connected via a router 14, an integrated services digital network (hereinafter called ISDN) 3, and connecting lines 41 and 42 to a PC 21 and telephone sets 22a - 22c connected to the LAN 20.

[0003]

According to the system shown in FIG. 7, the method of communication between LAN telephones that was conventionally realized using PCs is explained with reference to the sequence chart of FIG. 8 (VoIP system). The LAN telephone 22' of the caller party generates a call to the address of the LAN telephone 12', and the LAN telephone receiving the call returns a "reply (call OK)" to the LAN telephone 22', thereby starting the call, and after the call is finished, the call is disconnected.

[0004]

According to the prior art, the communication method for realizing calls between LAN telephones connected either to the same local area network or to other local area networks having different subnet addresses via a subscriber line can be applied

for communication designating a specific address, and as shown in FIG. 8, the call is generated, replied, connected, and disconnected. However, there are no proposals related to the communication method enabling communication between unspecified telephones connected to the local area network, such as communication between extension telephones (conventional branch-connected telephones). Further, there were no considerations on how to transfer calls.

[0005]

[Problem to be solved by the Invention]

The present invention provides a new communication system, and the object of the invention is to provide a repeating device, a telephone set and a recording medium enabling communication between LAN telephones that are either connected via communication lines to the same local area network or to local area networks having different subnet addresses, wherein the call from the LAN telephone can be realized without having to specify the receiver of the call.

[0006]

[Means to Solve the Problem]

The present invention provides a repeating device for relaying communication to a plurality of receiver-side telephones connected to a local area network, the repeating device comprising a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out

of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected receiver-side telephone to a caller-side telephone.

[0007]

Moreover, the present invention provides a repeating device further comprising a function for receiving a transfer request from a user.

[0008]

Further, the present invention provides a telephone capable of generating a call to a plurality of receiver-side telephones being connected to a local area network without designating the address of the receiver, the telephone comprising a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for generating a call addressed to said selected telephone.

[0009]

Even further, the present invention provides a telephone connected to a local area network, the telephone comprising upon receiving a transfer request from a user a function for requesting a response from a plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side

telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected telephone to a caller-side telephone.

[0010]

Moreover, the present invention provides a recording medium capable of being read by a computer and storing a program to be executed by said computer, said recording medium used either for a device for relaying communication to a plurality of receiver-side telephones being connected to a local area network, a telephone being connected to a local area network, or a telephone capable of generating a call to a plurality of receiver-side telephones being connected to a local area network without having to specify the address of the receiver telephone, wherein the recording medium comprises any of the following sets of functions: a function for requesting a response from said plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected receiver-side telephone to a caller-side telephone; a function for requesting a response from said plurality of receiver-side telephones indicating whether or not they are capable of connecting a call, a function for selecting a telephone to which the call is to be connected out of the plurality of receiver-side telephones that responded, and a function for generating a call



addressed to said selected telephone; or a function for requesting upon receiving a transfer request from a user a response from a plurality of receiver-side telephones indicating their availability to receive a call, a function for selecting out of the plurality of receiver-side telephones that responded a telephone to which the call is to be connected, and a function for notifying the address of the selected telephone to a caller-side telephone.

[0011]

#### [Preferred Embodiments of the Present Invention]

The preferred embodiments according to the present invention will now be explained.

FIGS. 1 through 7 are referred to in explaining the embodiments of the repeating device (router), the telephone, and the recording medium according to the present invention. FIG. 1 is an explanatory view showing the functional structure of a logical block of the router according to embodiment 1. FIG. 2 is an explanatory view showing one example of the operation of the router according to embodiment 1. FIG. 3 is an explanatory view showing the functional structure of the logical block of the LAN telephone according to embodiment 2. FIG. 4 is an explanatory view showing one example of the operation of the LAN telephone according to embodiment 2. FIG. 5 is an explanatory view showing one example of the operation of the LAN telephone according to embodiment 3. FIG. 6 is an explanatory view showing one example of the operation of the

router according to embodiment 4. FIG. 7 is an explanatory view showing the minimum system environment in which the LAN telephone and the repeating device operate.

[0012]

Embodiment 1 will now be explained. A router 14 which functions as the repeating device in the present embodiment comprises a function for requesting to a plurality of receiver telephones to reply whether they are capable of receiving a call or not, a function for selecting the telephone to connect the call to out of the plurality of receiver telephones that responded, and a function for notifying the address of the selected receiver telephone to the caller telephone. The functional structure of the logical block of the router 14 according to the present embodiment comprises, as shown in FIG. 1, a CPU 141 having a structure of a microcomputer that facilitates the send-receive of communication data by controlling the whole unit, a RAM 142 functioning as a memory for logical memory, an EEPROM 143 which is a storage memory, an LED 144 and an LCD 145 that show the status of the present unit, a subscriber line (ISDN) and a 10 BASE-T (LAN), and a clock 146. The router 14 further comprises a controller 150 that physically controls the subscriber line (ISDN), a controller 151 that physically controls the 10 BASE-T, and a controller 152 that physically controls the RS-232C. Moreover, the router 14 comprises a network controller 147 and a 10 BASE-T controller 151 for controlling the data being sent to or received from the

subscriber line (ISDN), a LAN controller 148 that controls the data being sent to or received from the 10 BASE-T (LAN), and a RAM 149 which is used as the memory in which the network controller 147 or the LAN controller 148 store the send-receive data.

[0013]

One example of the environment in which the router 14 of embodiment 1 is used is shown in FIG. 7. FIG. 7 shows the minimum system environment in which the LAN telephones etc. operate, constituted of local area networks LAN 10 and LAN 20 having different subnet addresses, communication terminal PCs (personal computers) 11 and 21 connected to each LAN, ISDN circuits 41 and 42, an ISDN 3, routers 14 and 24 utilized as repeating devices, receiver-side LAN telephones 12a - 12c, and caller-side LAN telephones 22a - 23.

[0014]

One example of the operation of router 14 in embodiment 1 is explained with reference to FIG. 2. In the embodiment, router 14 receives communication from one of the LAN telephones (in which the address is not specified). When a call addressed to the router 14 is received from the caller LAN telephone 22a, the router 14 receiving the call determines that since the call is addressed to the router 14 the call does not specify the receiver LAN telephone, and the router 14 issues a broadcast for confirming to all the LAN telephones 12a - 12c whether they are capable of receiving a call or not, and waits for their reply.

Upon receiving the broadcast, each LAN telephone 12a - 12c rings a call bell, and if the user replies the LAN telephone returns a "reply (call available)" to the router 14 (in the present example, all the telephones 12a - 12c are available for the call). Upon receiving the call available reply, the router 14 selects one telephone out of the LAN telephones 12a - 12c that responded, so as to connect the call (the selection can be performed for example based on the priorities set to the LAN telephones). In the present example, LAN telephone 12a is selected, and the address of the LAN telephone 12a is notified to the caller LAN telephone 22a. Upon receiving the notice, the caller LAN telephone 22a generates a call addressed to the LAN telephone 12a. When the LAN device 12a receives the call, it returns a "reply (call OK)". Upon receiving the "reply (call OK)", the caller LAN telephone 22a starts the communication using the VoIP protocol. Thus, the router 14 is capable of selecting the LAN telephone 12a, and the caller LAN telephone 22a can communicate with the selected LAN telephone 12a.

[0015]

Embodiment 2 will now be explained. The telephone according to the present embodiment is capable of generating a call to a plurality of receiver telephones connected to a local area network without specifying the receiver, and comprises a function for requesting to a plurality of receiver telephones to reply their availability to receive a call, a function for selecting the telephone to connect the call to out of the

plurality of receiver telephones that responded, and a function for generating the call to the address of the selected telephone. The telephone 22a according to the present embodiment is similar to the receiver LAN telephone 12a, and the function structure of the logical block thereof is shown in FIG. 3. The LAN telephone of embodiment 2 comprises a CPU 121 having a structure of a microcomputer that facilitates the send-receive of communication data by controlling the whole unit, a RAM 122 functioning as a memory for logical memory, an EEPROM 123 which is a storage memory, an LED 124 and an LCD 125 that show the status of the present unit, a subscriber line (ISDN) and a 10 BASE-T (LAN), and a clock 126. Further, the present telephone comprises a LAN controller 127 that controls the send-receive data with the 10 BASE-T (LAN), and a controller 128 for physically controlling the 10 BASE-T. The telephone further comprises a microphone 129 and a speaker 130 that control the voice from the exterior.

[0016]

One example of the operation of the telephone in embodiment 2 is explained with reference to FIG. 4. In the embodiment, the caller LAN telephone 22a which is the telephone according to the present embodiment issues a broadcast without designating the address confirming to all the LAN telephones 12a - 12c connected to the LAN 10 whether they are capable of receiving a call or not, and waits for their reply. Upon receiving the broadcast, each LAN telephone 12a - 12c rings a

call bell, and if the user replies the LAN telephone returns a "reply (call available)" to the receiver LAN telephone 22a (in the present example, all the telephones 12a - 12c are available for the call). Upon receiving the call available reply, the caller LAN telephone 22a selects one telephone out of the LAN telephones 12a - 12c that responded, so as to connect the call (the selection can be performed for example based on the priorities set to the LAN telephones). In the present example, LAN telephone 12a is selected, and the caller LAN telephone 22a generates a call addressed to the LAN telephone 12a. When the LAN device 12a receives the call, it returns a "reply (call OK)". Upon receiving the "reply (call OK)", the caller LAN telephone 22a starts the communication using the VoIP protocol. Thus, the caller LAN telephone 22a is capable of selecting the LAN telephone 12a and communicating with the selected LAN telephone 12a.

[0017]

Embodiment 3 will now be explained. The telephone according to the present embodiment comprises a function for requesting upon receiving a transfer order from a user a response to a plurality of receiving telephones asking their availability to receive a call, a function for selecting a telephone for connecting the call out of the receiving telephones that responded, and a function for notifying the address of the selected telephone to the caller telephone. When there is no address designated by the user when the user orders

a transfer, the telephone itself can search for the destination of transfer. As shown in FIG. 3, the functional structure of the logical block of the telephone is similar to that of embodiment 2, and the explanation thereof is omitted.

[0018]

The operation of the telephone according to embodiment 3 will be explained with reference to FIG. 5. While a call is connected between the caller LAN telephone 22a and the receiver LAN telephone 12a of the present embodiment, if the user orders transfer at the LAN telephone 12a and when no transfer address is designated, the LAN telephone 12a issues a broadcast confirming to all the LAN telephones 12 connected to the LAN 10 (excluding itself, which is telephone 12a) whether they are available for receiving a call, and waits for their reply. Upon receiving the broadcast, each LAN telephone 12b - 12c rings a call bell, and if the user replies the LAN telephone returns a "reply (call available)" to the LAN telephone 12a (in the present example, all the telephones are available for the call). Upon receiving the call available reply, the caller LAN telephone 12a selects one telephone out of the LAN telephones that responded, so as to connect the call (the selection can be performed for example based on the priorities set to the LAN telephones). In the present example, LAN telephone 12c is selected, and the address of the LAN telephone 12c is notified to the caller LAN telephone 22a. When the LAN telephone 22a receives the notice, it disconnects the call with the LAN

telephone 12a and generates a call addressed to the LAN telephone 12c. When the LAN telephone 12c receives the call, it returns a "reply (call OK)". Upon receiving the "reply (call OK)", the caller LAN telephone 22a starts the communication using the VoIP protocol, and the transfer process is completed. Thus, the LAN telephone 12a can select the LAN telephone 12c, and the caller LAN telephone 22a can communicate with the selected LAN telephone 12c.

[0019]

Embodiment 4 will now be explained. The router functioning as the repeating device in the present embodiment comprises a function for requesting a reply to a plurality of receiving telephones asking their availability to receive a call, a function for selecting one telephone out of the receiving telephones that replied for connecting the call, a function for notifying the address of the selected receiving telephone to the caller telephone, and a function for receiving the transfer request from the user. The present router differs from the router of embodiment 1 in that it holds a function for receiving the transfer request from the user. When the user requests a transfer without designating the receiver address from the caller telephone and the telephone sends the transfer request to the repeating device, the repeating device of the present embodiment can search for a transfer destination and process the transfer. The functional block of the present embodiment is similar to that of embodiment 1 as shown in FIG. 1, and the



explanation thereof is omitted.

[0020]

One example of the operation by the repeating device according to embodiment 4 will be explained with reference to FIG. 6. While a call is connected between the caller LAN telephone 22a and the receiver LAN telephone 12a, if the user orders transfer at the LAN telephone 12a and when no transfer address is designated, the LAN telephone 12a transmits a "transfer request (no transfer address designated)" to the router 14 of the present embodiment. Upon receiving the "transfer request (no transfer address designated)", the router 14 issues a broadcast confirming to all the LAN telephones 12 connected to the LAN 10 (excluding telephone 12a connected to the call) whether they are available for receiving a call, and waits for their reply. Upon receiving the broadcast, each LAN telephone 12b - 12c rings a call bell, and if the user replies the LAN telephone returns a "reply (call available)" to the router 14. In the present example, all the telephones are available for the call. Upon receiving the call available reply, the router 14 selects one telephone out of the LAN telephones that responded, so as to connect the call (the selection can be performed for example based on the priorities set to the LAN telephones). In the present example, LAN telephone 12c is selected, and the address of the LAN telephone 12c is notified to the caller LAN telephone 22a. When the LAN telephone 22a receives the notice, it disconnects the call with the LAN

telephone 12a and generates a call addressed to the LAN telephone 12c. When the LAN telephone 12c receives the call, it returns a "reply (call OK)". Upon receiving the "reply (call OK)", the caller LAN telephone 22a starts the communication using the VoIP protocol, and the transfer process is completed. Thus, the router 14 can select the LAN telephone 12c, and the caller LAN telephone 22a can communicate with the selected LAN telephone 12c.

[0021]

The above embodiments explained the cases where the invention is applied to the repeating device and the telephones, but it is also possible to store to a recording medium that can be read by a computer (for example, a CD-ROM) a program that realizes any of the following sets of functions by the computer: a function for requesting a response to the plurality of receiver telephones asking their availability to receive a call, a function for selecting the telephone for connecting the call out of the receiving telephones that responded, and a function for notifying the address of the selected receiver telephone to the caller telephone; a function for requesting a response to the plurality of receiver telephones asking their availability to receive a call, a function for selecting the telephone for connecting the call out of the receiving telephones that responded, and a function for generating a call to the address of the selected telephone; or a function for requesting upon receiving the transfer request from a user a

response to the plurality of receiver telephones asking their availability to receive a call, a function for selecting the telephone for connecting the call out of the receiving telephones that responded, and a function for notifying the address of the selected telephone to the caller telephone. By using this recording medium, a device for relaying the call addressed to a plurality of receiver telephones connected to a local area network, a telephone being connected to the local area network, and a telephone capable of generating a call to the plurality of receiver telephones connected to the local area network without designating the receiver address can all function as the repeating device and the telephone set according to the present invention.

[0022]

[Effect of the Invention]

According to the present invention, in a communication system enabling communication between LAN telephones by providing a relay device in a local area network or by relaying local area networks that have different subnet addresses by a communication line, the present invention enables to provide a repeating device and a telephone that are capable of selecting the receiver telephone without having to designate the receiver address.

[Brief Explanation of the Drawings]

[FIG. 1]

FIG. 1 is an explanatory view showing the functional

structure of a logical block of the router according to embodiment 1.

[FIG. 2]

FIG. 2 is an explanatory view showing one example of the operation of the router according to embodiment 1.

[FIG. 3]

FIG. 3 is an explanatory view showing the functional structure of a logical block of the LAN telephone according to embodiment 2.

[FIG. 4]

FIG. 4 is an explanatory view showing one example of the operation of the LAN telephone according to embodiment 2.

[FIG. 5]

FIG. 5 is an explanatory view showing one example of the operation of the LAN telephone according to embodiment 3.

[FIG. 6]

FIG. 6 is an explanatory view showing one example of the operation of the router according to embodiment 4.

[FIG. 7]

FIG. 7 is an explanatory view showing the minimum system environment for operating the LAN telephones and the repeating device.

[FIG. 8]

FIG. 8 is an explanatory view showing the operation of the LAN telephone according to the prior art.

[References]

10, 20 local area network  
11, 21 personal computer  
12, 12a-12c, 22a-22c local area network telephone  
121 CPU  
122 RAM  
123 EEPROM  
124 LED  
125 LCD  
126 clock  
127 LAN controller  
128 10 BASE-T controller  
129 microphone  
130 speaker  
14, 24 router  
141 CPU  
142 RAM  
143 EEPROM  
144 LED  
145 LCD  
146 clock  
147 network controller  
148 LAN controller  
149 RAM  
150 I interface controller  
151 10 BASE-T controller  
152 RS-232C controller

3 ISDN network

41, 42 ISDN circuit

[Document] Summary

[Summary]

[Object] To provide a relay device, a telephone set or a recording medium that is capable of generating a call without designating the receiver when connecting a call between LAN telephones that are connected to a local area network or connected to local area networks that have different subnet addresses and relayed by a communication line.

[Means to Solve the Problem] A repeating device 14 for relaying the call to a plurality of receiver telephones 12a-12c that are connected to a local area network, comprising a function for requesting a reply to the plurality of receiver telephones 12a-12c, a function for selecting the destination of the call out of the receiver telephones 12a-12c that responded, and a function for notifying the address of the selected receiver telephone 12a to the caller telephone 22a. Further, the present repeating device comprises a function for receiving the transfer request from a user.

[Selected Drawing] FIG. 2

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**